

PT9101 (Extended Range)

Extended Ranges • Voltage Divider

Absolute Linear Position to 1700 inches (4300 cm)

Stroke Range Options: 0-600 to 0-1700 inches

VLS Option To Prevent Free-Release Damage

IP68 • NEMA 6 Protection



GENERAL


Full Stroke Range Options (on this datasheet)	0-600 to 0-1700 inches
Output Signal	voltage divider (potentiometer)
Accuracy	$\pm 0.10\%$ full stroke
Repeatability	$\pm 0.02\%$ full stroke
Resolution	essentially infinite
Measuring Cable Options	stainless steel or thermoplastic
Enclosure Material	powder-painted aluminum or 303 stainless steel
Sensor	plastic-hybrid precision potentiometer
Potentiometer Cycle Life	$\geq 250,000$
Maximum Retraction Acceleration	see ordering information
Maximum Velocity	see ordering information
Weight, Aluminum (Stainless Steel) Enclosure	14 lbs. (28 lbs.) max.

ELECTRICAL

Input Resistance Options	500, 1K, 5K, 10K Ω , bridge
Power Rating, Watts	2.0 at 70°F derated to 0 at 250° F
Recommended Maximum Input Voltage	30V (AC/DC)
Output Signal Change Over Full Stroke Range	94% $\pm 4\%$ of input voltage

ENVIRONMENTAL


Enclosure	NEMA 4/4X/6, IP 67/68
Operating Temperature	-40° to 200°F (-40° to 90°C)
Vibration	up to 10 g to 2000 Hz maximum



The PT9101 is a work-horse for demanding long-range applications requiring a linear position measurements in ranges up to 1700 inches. Available with either a 500, 1K, 5K, or 10K ohm potentiometer, the PT9101 operates with any basic panel meter or programmable controller.


As a member of Celesco's innovative family of NEMA 4 rated cable-extension transducers, the PT9101 offers numerous benefits. It installs in minutes, works without perfect parallel alignment, and when it's stainless-steel cable is retracted, it measures only 6".

Output Signal:




-- bridge circuit option available, see ordering information


Outline Drawing



mounting hole detail




eyelet detail



A DIMENSION

RANGE	inches [mm]
600	1.76 [44,7]
800	1.58 [40,1]
1000	1.98 [50,2]
1200	1.98 [50,2]
1500	1.86 [47,2]
1700	2.11 [53,6]



DIMENSIONS ARE IN INCHES [MM]
tolerances are 0.03 IN. [0.5 MM] unless otherwise noted.

* tolerance = +.005 -.001 [+.13 -.03]
** tolerance = +.005 -.005 [+1.3 -.13]

VLS Option - Free Release Protection

The patented Celesco Velocity Limiting System (VLS) is an option for PT9000 Series cable extension transducers that limits cable retraction to a safe 40 to 55 inches per second for the single spring option and 40 to 80 inches per second for the higher tension dual spring option.

The VLS option prevents the measuring cable from ever reaching a damaging velocity during an accidental free release. This option is ideal for mobile applications that require frequent cable disconnection and reconnection. It prevents expensive unscheduled downtime due to accidental cable mishandling or attachment failure.

How To Configure Model Number for VLS Option:

VLS 9101- — **R** — **A** — **B** — **C** — **D** — **E** — **F** — **G**

creating VLS model number (example)...

1. select PT9101 model **PT9101-1200-111-1110**
2. remove "PT" from the model number **9101-1200-111-1110**
3. add "VLS" **VLS + 9101-1200-111-1110**
4. completed model number ! **VLS9101-1200-111-1110**

Electrical Connection:

1 order code:			2			3			4		
6-pin plastic connector w/mating plug IP 67, NEMA 4X**, 6			10-ft. [3 M] waterproof cable IP 67, NEMA 4X**, 6			6-pin metal connector w/mating plug IP 65, NEMA 4			25-ft. [7.5 M] instrumentation cable IP 67, NEMA 6		
5 order code:			6			7					
100-ft. [30 M] waterproof cable IP 67, NEMA 4X**, 6			10-ft. [3 M] pressure tested* waterproof cable IP 68, NEMA 4X**, 6P			100-ft. [30 M] pressure tested* waterproof cable IP 68, NEMA 4X**, 6P					
6-pin Mating Plug						Waterproof Cable			Instrumentation Cable		
pin	standard	bridge				color code	standard	bridge	color code	standard	bridge
A	+ in	+ in				WHITE	+ in	n/a	RED	+ in	+ in
B	common	- in				BLACK	common	n/a	BLACK	common	- in
C	+ out	- out				GREEN	+ out	n/a	GREEN	+ out	+ out
D	-	+ out							WHITE	-	- out

Notes: *—Test pressure: 100 feet [30 meters] H₂O (40 PSID); Test Medium: Air; Duration: 2 hours. **—NEMA 4X applies to stainless steel enclosure only.

version: 8.0 last updated: April 10, 2013